



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Version 1.0

Design, Installation & Application Guide

Nano Bubble Nozzle Series

Puroxi® Technical Product Manual

Date: Thursday, September 10, 2026

Subject: Puroxi® Nano Bubble Nozzle Technical Product Manual

Thank you for your interest in Puroxi Nano Bubble technology. Attached is the initial technical product manual summarizing our standard nozzle range. This document is intended to provide an overview of the available models, flow capacities, pressure requirements, oxygen transfer performance, ozone transfer capability, recommended pump sizes, materials and ordering information.

This catalogue is the foundation of a much larger manual that will also include dimensional drawings, installation schematics, performance curves, product photographs, and application guides.

Thank you for the opportunity to understand your water.

Sincerely,

Puroxi Pure Water Global Inc.

Technical Note

This publication is intended as a technical product manual and application guide. It has been developed to assist customers, consultants, contractors, operators, and system designers in selecting and applying Puroxi® Nano Bubble Nozzles. All recommendations are based on product design characteristics, field experience, and application knowledge. Final system design should always consider the specific operating conditions of each installation.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998



PUROXI® NANO BUBBLE NOZZLE FAMILY

Engineered for Superior Gas Transfer. Built for Reliability. Designed for Performance.



MAXIMUM GAS TRANSFER
High efficiency nano
bubble generation



SUPERIOR PERFORMANCE
Greater oxygen transfer
and water quality



BUILT TO LAST
Corrosion resistant
and maintenance friendly



NATURAL SOLUTION
Improves water quality
the natural way



Puroxi® Nano Bubble Nozzles are available in a complete range of flow capacities to suit every application requirement. From small ponds and tanks to large-scale municipal and industrial systems, Puroxi® delivers the right solution for maximum oxygen transfer, improved water quality, and long-term operational efficiency.



DESIGNED & SUPPORTED
IN CANADA



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Table of Contents

MNB02	4
MNB06	5
MNB09	6
MNB20	7
MNB30	8
MNB40	9
MNB40S	10
MNB50	11
MNB60	12
MNB60S	13
MNB80	14
MNB100	15
MNB120	16
MNB150	17
MNB180	18
MNB250	19
MNB300	20
MNB400	21
VEN-X Milli-Microbubbler Series	22
Current Model, Material & Accessory Options	23



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Puroxi® Nano Bubble Nozzle – MNB02

Specification	Value
Flow Capacity (m ³ /h)	2
Connections	1-inch pipe size (Outer diameter = 1.315 inch) No thread on nozzle ends
Recommended Pump	80–150 W
Max Pressure (psi)	100
Pure Oxygen Transfer (grams/hr)	16–48
Ozone Transfer (L/hr)	18–54
Natural Air O ₂ (salinity/fresh grams/hr)	13–15 / 10–12
Materials	UPVC, CPVC+PTFE, PTFE, SS304, SS316
Accessories	Gas fittings, 5 m tubing, flowmeter
Advantages	High oxygen transfer, low maintenance, no moving parts
Pricing	Contact Puroxi for current system selection and pricing.

Ordering Information: Contact Puroxi with water volume, application, water chemistry and desired turnover rate for final nozzle selection.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Puroxi® Nano Bubble Nozzle – MNB06

Specification	Value
Flow Capacity (m ³ /h)	6
Connections	1 1/4-inch pipe size (Outer diameter = 1.66 inch) No thread on nozzle ends
Recommended Pump	250–350 W
Max Pressure (psi)	100
Pure Oxygen Transfer (grams /hr)	48–144
Ozone Transfer (L/hr)	54–162
Natural Air O ₂ (salinity/fresh grams /hr)	39–45 / 30–36
Materials	UPVC, CPVC+PTFE, PTFE, SS304, SS316
Accessories	Gas fittings, 5 m tubing, flowmeter
Advantages	High oxygen transfer, low maintenance, no moving parts
Pricing	Contact Puroxi for current system selection and pricing.

Ordering Information: Contact Puroxi with water volume, application, water chemistry and desired turnover rate for final nozzle selection.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Puroxi® Nano Bubble Nozzle – MNB09

Specification	Value
Flow Capacity (m ³ /h)	9
Connections	1 1/4-inch pipe size (Outer diameter = 1.66 inch) No thread on nozzle ends
Recommended Pump	450–550 W
Max Pressure (psi)	100
Pure Oxygen Transfer (grams /hr)	70–210
Ozone Transfer (L/hr)	80–240
Natural Air O ₂ (salinity/fresh grams /hr)	65–75 / 50–60
Materials	UPVC, CPVC+PTFE, PTFE, SS304, SS316
Accessories	Gas fittings, 5 m tubing, flowmeter
Advantages	High oxygen transfer, low maintenance, no moving parts
Pricing	Contact Puroxi for current system selection and pricing.

Ordering Information: Contact Puroxi with water volume, application, water chemistry and desired turnover rate for final nozzle selection.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Puroxi® Nano Bubble Nozzle – MNB20

Specification	Value
Flow Capacity (m ³ /h)	20
Connections	1 1/2-inch pipe size (Outer diameter = 1.90 inch) No thread on nozzle ends
Recommended Pump	750–850 W
Max Pressure (psi)	100
Pure Oxygen Transfer (grams /hr)	140–520
Ozone Transfer (L/hr)	160–480
Natural Air O ₂ (salinity/fresh grams /hr)	100–120 / 70–90
Materials	UPVC, CPVC+PTFE, PTFE, SS304, SS316
Accessories	Gas fittings, 5 m tubing, flowmeter
Advantages	High oxygen transfer, low maintenance, no moving parts
Pricing	Contact Puroxi for current system selection and pricing.

Ordering Information: Contact Puroxi with water volume, application, water chemistry and desired turnover rate for final nozzle selection.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Puroxi® Nano Bubble Nozzle – MNB30

Specification	Value
Flow Capacity (m ³ /h)	30
Connections	2-inch pipe size (Outer diameter = 1.913inch) No thread on nozzle ends
Recommended Pump	1.1–1.5 kW
Max Pressure (psi)	100
Pure Oxygen Transfer (grams /hr)	210–630
Ozone Transfer (L/hr)	240–720
Natural Air O ₂ (salinity/fresh grams /hr)	170–200 /120–140
Materials	UPVC, CPVC+PTFE, PTFE, SS304, SS316
Accessories	Gas fittings, 5 m tubing, flowmeter
Advantages	High oxygen transfer, low maintenance, no moving parts
Pricing	Contact Puroxi for current system selection and pricing.

Ordering Information: Contact Puroxi with water volume, application, water chemistry and desired turnover rate for final nozzle selection.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Puroxi® Nano Bubble Nozzle – MNB40

Specification	Value
Flow Capacity (m ³ /h)	40
Connections	2-inch pipe size (Outer diameter = 2.50 inch) No thread on nozzle ends, no flanges included
Recommended Pump	1.5–2 kW
Max Pressure (psi)	100
Pure Oxygen Transfer (grams /hr)	320–960
Ozone Transfer (L/hr)	360–1080
Natural Air O ₂ (salinity/fresh grams /hr)	225–270 /160–190
Materials	UPVC, CPVC+PTFE, PTFE, SS304, SS316
Accessories	Gas fittings, 5 m tubing, flowmeter
Advantages	High oxygen transfer, low maintenance, no moving parts
Pricing	Contact Puroxi for current system selection and pricing.

Ordering Information: Contact Puroxi with water volume, application, water chemistry and desired turnover rate for final nozzle selection.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Puroxi® Nano Bubble Nozzle – MNB40S

Specification	Value
Flow Capacity (m ³ /h)	40
Connections	3-inch pipe size (Outer diameter = 3.50 inch) No thread on nozzle ends, no flanges included
Recommended Pump	1.5–2 kW
Max Pressure (psi)	100
Pure Oxygen Transfer (grams /hr)	320–960
Ozone Transfer (L/hr)	360–1080
Natural Air O ₂ (salinity/fresh grams /hr)	225–270 /160–190
Materials	UPVC, CPVC+PTFE, PTFE, SS304, SS316
Accessories	Gas fittings, 5 m tubing, flowmeter
Advantages	High oxygen transfer, low maintenance, no moving parts
Pricing	Contact Puroxi for current system selection and pricing.

Ordering Information: Contact Puroxi with water volume, application, water chemistry and desired turnover rate for final nozzle selection.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Puroxi® Nano Bubble Nozzle – MNB50

Specification	Value
Flow Capacity (m ³ /h)	50
Connections	3-inch pipe size (Outer diameter = 3.50 inch) No thread on nozzle ends, no flanges included
Recommended Pump	2.2–2.5 kW
Max Pressure (psi)	100
Pure Oxygen Transfer (grams /hr)	400–1200
Ozone Transfer (L/hr)	450–1350
Natural Air O ₂ (salinity/fresh grams /hr)	290–310 /190–210
Materials	UPVC, CPVC+PTFE, PTFE, SS304, SS316
Accessories	Gas fittings, 5 m tubing, flowmeter
Advantages	High oxygen transfer, low maintenance, no moving parts
Pricing	Contact Puroxi for current system selection and pricing.

Ordering Information: Contact Puroxi with water volume, application, water chemistry and desired turnover rate for final nozzle selection.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Puroxi® Nano Bubble Nozzle – MNB60

Specification	Value
Flow Capacity (m ³ /h)	60
Connections	3-inch pipe size (Outer diameter = 3.50 inch) No thread on nozzle ends, no flanges included
Recommended Pump	3–3.5 kW
Max Pressure (psi)	300
Pure Oxygen Transfer (grams /hr)	480–1440
Ozone Transfer (L/hr)	540–1620
Natural Air O ₂ (salinity/fresh grams /hr)	350–480 /230–350
Materials	UPVC, CPVC+PTFE, PTFE, SS304, SS316
Accessories	Gas fittings, 5 m tubing, flowmeter
Advantages	High oxygen transfer, low maintenance, no moving parts
Pricing	Contact Puroxi for current system selection and pricing.

Ordering Information: Contact Puroxi with water volume, application, water chemistry and desired turnover rate for final nozzle selection.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Puroxi® Nano Bubble Nozzle – MNB60S

Specification	Value
Flow Capacity (m ³ /h)	60
Connections	3-inch pipe size (Outer diameter = 3.50 inch) No thread on nozzle ends, no flanges included
Recommended Pump	3–3.5 kW
Max Pressure (psi)	300
Pure Oxygen Transfer (grams /hr)	480–1440
Ozone Transfer (L/hr)	540–1620
Natural Air O ₂ (salinity/fresh grams /hr)	350–480 /230–350
Materials	UPVC, CPVC+PTFE, PTFE, SS304, SS316
Accessories	Gas fittings, 5 m tubing, flowmeter
Advantages	High oxygen transfer, low maintenance, no moving parts
Pricing	Contact Puroxi for current system selection and pricing.

Ordering Information: Contact Puroxi with water volume, application, water chemistry and desired turnover rate for final nozzle selection.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Puroxi® Nano Bubble Nozzle – MNB80

Specification	Value
Flow Capacity (m ³ /h)	80
Connections	4-inch pipe size (Outer diameter = 4.50 inch) No thread on nozzle ends, no flanges included
Recommended Pump	5–5.5 kW
Max Pressure (psi)	250
Pure Oxygen Transfer (grams /hr)	600–1900
Ozone Transfer (L/hr)	700–2000
Natural Air O ₂ (salinity/fresh grams /hr)	440–500 /300–380
Materials	UPVC, CPVC+PTFE, PTFE, SS304, SS316
Accessories	Gas fittings, 5 m tubing, flowmeter
Advantages	High oxygen transfer, low maintenance, no moving parts
Pricing	Contact Puroxi for current system selection and pricing.

Ordering Information: Contact Puroxi with water volume, application, water chemistry and desired turnover rate for final nozzle selection.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Puroxi® Nano Bubble Nozzle – MNB100

Specification	Value
Flow Capacity (m ³ /h)	100
Connections	4-inch pipe size (Outer diameter = 4.50 inch) No thread on nozzle ends, no flanges included
Recommended Pump	5.5–7.5 kW
Max Pressure (psi)	250
Pure Oxygen Transfer (grams /hr)	800–2400
Ozone Transfer (L/hr)	900–2600
Natural Air O ₂ (salinity/fresh grams /hr)	580–620 /380–420
Materials	UPVC, CPVC+PTFE, PTFE, SS304, SS316
Accessories	Gas fittings, 5 m tubing, flowmeter
Advantages	High oxygen transfer, low maintenance, no moving parts
Pricing	Contact Puroxi for current system selection and pricing.

Ordering Information: Contact Puroxi with water volume, application, water chemistry and desired turnover rate for final nozzle selection.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Puroxi® Nano Bubble Nozzle – MNB120

Specification	Value
Flow Capacity (m ³ /h)	120
Connections	4-inch pipe size (Outer diameter = 4.50 inch) No thread on nozzle ends, no flanges included
Recommended Pump	7.5–9 kW
Max Pressure (psi)	250
Pure Oxygen Transfer (grams /hr)	960–2880
Ozone Transfer (L/hr)	1000–3200
Natural Air O ₂ (salinity/fresh grams /hr)	700–960 /460–700
Materials	UPVC, CPVC+PTFE, PTFE, SS304, SS316
Accessories	Gas fittings, 5 m tubing, flowmeter
Advantages	High oxygen transfer, low maintenance, no moving parts
Pricing	Contact Puroxi for current system selection and pricing.

Ordering Information: Contact Puroxi with water volume, application, water chemistry and desired turnover rate for final nozzle selection.

- ☐ Smaller MNB models typically have two gas ports.
- ☐ MNB120 and Larger models, including the MNB120 and above, have multiple gas ports around the nozzle.
- ☐ Air or oxygen must be distributed to every gas port on the selected model.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Puroxi® Nano Bubble Nozzle – MNB150

Specification	Value
Flow Capacity (m ³ /h)	150
Connections	4-inch pipe size (Outer diameter = 4.50 inch) No thread on nozzle ends, no flanges included
Recommended Pump	TBD
Max Pressure (psi)	250
Pure Oxygen Transfer (grams /hr)	See engineering
Ozone Transfer (L/hr)	See engineering
Natural Air O ₂ (salinity/fresh grams /hr)	See engineering
Materials	UPVC, CPVC+PTFE, PTFE, SS304, SS316
Accessories	Gas fittings, 5 m tubing, flowmeter
Advantages	High oxygen transfer, low maintenance, no moving parts
Pricing	Contact Puroxi for current system selection and pricing.

Ordering Information: Contact Puroxi with water volume, application, water chemistry and desired turnover rate for final nozzle selection.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Puroxi® Nano Bubble Nozzle – MNB180

Specification	Value
Flow Capacity (m ³ /h)	180
Connections	4-inch pipe size (Outer diameter = 4.50 inch) No thread on nozzle ends, no flanges included
Recommended Pump	TBD
Max Pressure (psi)	250
Pure Oxygen Transfer (grams /hr)	See engineering
Ozone Transfer (L/hr)	See engineering
Natural Air O ₂ (salinity/fresh grams /hr)	See engineering
Materials	UPVC, CPVC+PTFE, PTFE, SS304, SS316
Accessories	Gas fittings, 5 m tubing, flowmeter
Advantages	High oxygen transfer, low maintenance, no moving parts
Pricing	Contact Puroxi for current system selection and pricing.

Ordering Information: Contact Puroxi with water volume, application, water chemistry and desired turnover rate for final nozzle selection.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Puroxi® Nano Bubble Nozzle – MNB250

Specification	Value
Flow Capacity (m ³ /h)	250
Connections	6-inch pipe size (Outer diameter = 6.625 inch) No thread on nozzle ends, no flanges included
Recommended Pump	20–22 kW
Max Pressure (psi)	250
Pure Oxygen Transfer (grams /hr)	1920–5760
Ozone Transfer (L/hr)	2000–6400
Natural Air O ₂ (salinity/fresh grams /hr)	1400–1920 /920–1400
Materials	UPVC, CPVC+PTFE, PTFE, SS304, SS316
Accessories	Gas fittings, 5 m tubing, flowmeter
Advantages	High oxygen transfer, low maintenance, no moving parts
Pricing	Contact Puroxi for current system selection and pricing.

Ordering Information: Contact Puroxi with water volume, application, water chemistry and desired turnover rate for final nozzle selection.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Puroxi® Nano Bubble Nozzle – MNB300

Specification	Value
Flow Capacity (m ³ /h)	300
Connections	6-inch pipe size (Outer diameter = 6.625 inch) No thread on nozzle ends, no flanges included
Recommended Pump	20–22 kW
Max Pressure (psi)	250
Pure Oxygen Transfer (grams /hr)	1920–5760
Ozone Transfer (L/hr)	2000–6400
Natural Air O ₂ (salinity/fresh grams /hr)	1400–1920 /920–1400
Materials	UPVC, CPVC+PTFE, PTFE, SS304, SS316
Accessories	Gas fittings, 5 m tubing, flowmeter
Advantages	High oxygen transfer, low maintenance, no moving parts
Pricing	Contact Puroxi for current system selection and pricing.

Ordering Information: Contact Puroxi with water volume, application, water chemistry and desired turnover rate for final nozzle selection.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Puroxi® Nano Bubble Nozzle – MNB400

Specification	Value
Flow Capacity (m ³ /h)	400
Connections	6-inch pipe size (Outer diameter = 6.625 inch) No thread on nozzle ends, no flanges included
Recommended Pump	By design
Max Pressure (psi)	150
Pure Oxygen Transfer (grams /hr)	Custom
Ozone Transfer (L/hr)	Custom
Natural Air O ₂ (salinity/fresh grams /hr)	Custom
Materials	UPVC, CPVC+PTFE, PTFE, SS304, SS316
Accessories	Gas fittings, 5 m tubing, flowmeter
Advantages	High oxygen transfer, low maintenance, no moving parts
Pricing	Contact Puroxi for current system selection and pricing.

Ordering Information: Contact Puroxi with water volume, application, water chemistry and desired turnover rate for final nozzle selection.

MNB120 to MNB150 Micro-Nanobubble nozzle SS304 – Contact Puroxi for pricing

MNB120 to MNB150 Micro-Nanobubble nozzle SS316 – Contact Puroxi for pricing

MNB250 to MNB300 Micro-Nanobubble nozzle SS304 – Contact Puroxi for pricing

MNB250 to MNB300 Micro-Nanobubble nozzle SS316 – Contact Puroxi for pricing

MNB400 Micro-Nanobubble nozzle SS304 – Contact Puroxi for pricing

MNB400Micro-Nanobubble nozzle SS316 – Contact Puroxi for pricing



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Puroxi® VEN-X Mili-Microbubbler Series

Model / Item	Specification	Pricing
MM3090	UPVC; 90 mm inlet / 60 mm outlet; smooth ends; includes 5 m polyurethane hose and bronze gas fittings	Contact Puroxi
MM2060	UPVC; 60 mm inlet / 49 mm outlet; smooth ends; includes 2 m polyurethane hose and bronze gas fittings	Contact Puroxi
MM1060	UPVC; 60 mm inlet / 34 mm outlet; smooth ends; includes 1 m polyurethane hose and bronze gas fittings	Contact Puroxi
4-Way 60 mm	Four-way discharge assembly for MM3090	Contact Puroxi
4-Way 49 mm	Four-way discharge assembly for MM2060	Contact Puroxi
4-Way 34 mm	Four-way discharge assembly for MM1060	Contact Puroxi

System selection and pricing: Contact Puroxi for current configuration, availability and quotation.



WhatsApp/Cell: +1 604 302 9424
 Office: +1 778 910 0355
 Fax: +1 778 244 4466
 Email: info@puroxi.com
 Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
 SINCE 1998

Current Model, Material & Accessory Options

Current UPVC Model	Flow	Selection
MNB02	2 m ³ /h	Contact Puroxi
MNB06	6 m ³ /h	Contact Puroxi
MNB09	9 m ³ /h	Contact Puroxi
MNB20	20 m ³ /h	Contact Puroxi
MNB30	30 m ³ /h	Contact Puroxi
MNB40S	40 m ³ /h	Contact Puroxi
MNB50	50 m ³ /h	Contact Puroxi
MNB60	60 m ³ /h	Contact Puroxi
MNB80	80 m ³ /h	Contact Puroxi
MNB100	100 m ³ /h	Contact Puroxi
MNB120	120 m ³ /h	Contact Puroxi
MNB160	160 m ³ /h	Contact Puroxi
MNB250	250 m ³ /h	Contact Puroxi
CPVC + PTFE Models	Pipe Size / OD	Material / Connection
MNB02-MNB04	1 in / 33.4 mm OD	CPVC + PTFE; smooth ends
MNB06-MNB09	1 1/4 in / 42 mm OD	CPVC + PTFE; smooth ends
MNB20	1 1/2 in / 48 mm OD	CPVC + PTFE; smooth ends
MNB30	2 in / 60 mm OD	CPVC + PTFE; smooth ends
MNB40	2 in / 60 mm OD	CPVC + PTFE; smooth ends
MNB40-MNB60	3 in / 90 mm OD	CPVC + PTFE; smooth ends
MNB80-MNB120	4 in / 114 mm OD	CPVC + PTFE; smooth ends
MNB200-MNB250	6 in / 168 mm OD	CPVC + PTFE; smooth ends

CPVC + PTFE models have a CPVC body with internal PTFE components and include stainless-steel gas fittings. Natural air, pure O₂ and O₃ enter through the gas ports. H₂O₂ and KMnO₄ must be dosed separately into the water line, not through the gas ports. Gas hose is not included; use 10 mm PTFE hose for ozone service.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Accessory	Application	Pricing
4-inch UPVC flange pair	For MNB150-MNB180; bolts not included	Contact Puroxi
6-inch UPVC flange pair	For MNB250-MNB300; bolts not included	Contact Puroxi
Polyurethane air hose	10 mm OD × 6.5 mm ID; MNB40 and above	Contact Puroxi
Air flowmeter	2-100 L/min or up to 8 m ³ /h	Contact Puroxi
PVDF one-way valve	For ozone service with 10 mm PTFE hose	Contact Puroxi
BFPOZO-10 / BFPO6	Backflow prevention options for ozone service	Contact Puroxi

General Ordering, Pressure Ratings & Delivery Information

- Pricing excludes shipping, GST (Canada), and, outside Canada, customs brokerage, VAT, import duties (where applicable), and shipping charges.
- Nano Bubble Nozzles are available in UPVC, CPVC + PTFE, PTFE, SS304 Stainless Steel, and SS316 Stainless Steel.
- UPVC nozzles from MNB02 to MNB50 typically have a maximum working pressure rating of 60–100 psi, depending on the model.
- UPVC nozzles from MNB60 are available with pressure ratings from 200–400 psi, depending on the application.
- UPVC nozzles from MNB80 to MNB400 are typically available with pressure ratings ranging from 250 psi down to 150 psi depending on model size.
- Higher pressure ratings can be manufactured for specific applications; however, additional manufacturing time may be required.
- Puroxi generally maintains inventory of the most common MNB02 through MNB120 models. Typical turnaround for stocked units is only a few business days.
- MNB150 through MNB400 generally require 20–30 days manufacturing lead time depending on model and quantity ordered. Single-unit orders may occasionally ship sooner.
- Courier transit time is additional to manufacturing lead time.
- A treated-water discharge manifold can direct flow into multiple zones.
- Additional branches create friction and resistance.
- A higher-capacity pump may be required.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

-
- Final selection must use the pump curve, complete-system total dynamic head, branch count and required flow at every outlet.
 - Gas Supply Tubing - Gas must be connected to every gas port on the selected Puroxi Nano Bubble Nozzle model. Each nozzle is supplied with **5 metres (16.4 ft)** of gas tubing. If additional tubing is required, it can be purchased locally from an industrial hose and fittings supplier. These suppliers are commonly available in most regions and stock suitable tubing for air and oxygen service.
 - Treated Discharge Manifold - A treated-water discharge manifold can direct nano-bubble-treated water toward multiple zones, but it adds friction and resistance. A higher-capacity pump may therefore be required, with final selection made from the pump performance curve using complete-system total dynamic head, number of branches and required flow at each outlet.

North American Connection Standards

To simplify installation and ensure compatibility with locally available piping systems, Puroxi® Nano Bubble Nozzles are available with different connection configurations depending on the material of construction.

UPVC and CPVC Nano Bubble Nozzles

For **North American installations**, Puroxi recommends that **UPVC and CPVC nano bubble nozzles be supplied with smooth socket (spigot) ends rather than threaded connections.**

The smooth ends are manufactured to standard pipe outside diameters and are designed to accept locally sourced slip fittings, including:

- Slip unions
- PVC or CPVC couplings
- Socket fittings
- Solvent-weld (glue) fittings
- Flange adapters
- Custom transition fittings

This approach allows installers to use locally available plumbing components that comply with regional plumbing standards and simplifies future maintenance or replacement.



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Puroxi Recommendation: For most North American PVC and CPVC installations, smooth-end connections provide a more versatile and reliable installation than threaded plastic connections.

PTFE, HDPE, POM, Stainless Steel 304 and Stainless Steel 316 Nano Bubble Nozzles

Nano bubble nozzles are manufactured from **PTFE, HDPE, POM, SS304, or SS316**.

Available connection standards include:

- NPT (National Pipe Thread)
- BSPT / BSPP (British Standard Pipe)
- JIS (Japanese Industrial Standard)
- ANSI / ASME
- DIN
- ISO
- Custom thread specifications (available at extra cost upon request)

The appropriate connection standard should be specified at the time of ordering to ensure compatibility with the customer's piping system.

Engineering Note

Always verify the following before ordering:

- Pipe material
- Pipe outside diameter
- Connection standard
- Pressure rating
- Temperature requirements
- Chemical compatibility
- Local plumbing or engineering codes

Selecting the correct connection type during the design stage helps reduce installation time and eliminates the need for unnecessary adapters or modifications in the field.

The Puroxi Integrated Oxidation Process™

Step 1 – Chemical Oxidation (Optional)



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

Hydrogen peroxide is metered into the water using a peristaltic dosing pump.

Depending on the application, ozone, oxygen, carbon dioxide, nitrogen, or other gases may also be used.

Step 2 – Nano Bubble Activation

The Puroxi Nano Bubble Nozzle creates billions of nano bubbles while simultaneously producing extremely intense mixing.

This rapidly disperses the hydrogen peroxide (or other treatment chemicals) uniformly throughout the water.

The persistent nano bubbles provide long-lasting dissolved oxygen and extended gas-liquid contact that can support oxidation processes and biological activity.

Step 3 – Water Quality Improvement

Depending on the application, the combined process may help:

Improve oxidation efficiency.

Increase dissolved oxygen.

Support beneficial aerobic bacteria.

Improve biological treatment.

Reduce odors.

Assist with COD and BOD reduction.

Improve sludge digestion.

Improve water clarity.

Enhance overall treatment performance.

Then we add what you've been saying all along:



WhatsApp/Cell: +1 604 302 9424
Office: +1 778 910 0355
Fax: +1 778 244 4466
Email: info@puroxi.com
Web: www.puroxi.com

PUROXI PURE WATER GLOBAL INC.

PURE WATER. SMARTER SOLUTIONS.
SINCE 1998

The treatment chemistry should be selected to suit the application. Hydrogen peroxide is often the preferred first choice because it is generally more economical, easier to store, safer to handle, and simpler to integrate than ozone. However, where higher oxidation potential is required, oxygen, ozone, carbon dioxide, nitrogen, or other gases can also be incorporated into the Puroxi Nano Bubble treatment process.